

# ***Self Positioning Astragal Seal***

by

VERNARD W. SANDERS

5

## **BACKGROUND OF THE INVENTION**

### **FIELD OF THE INVENTION**

10

The present invention relates generally to astragal seals and more particularly to self positioning astragal seals.

### **BACKGROUND ART**

15

Double entrance doorways are used in a large variety of residential homes and commercial buildings. Typically, an active door provides for day to day ingress and egress to and from the residential home or building, and an inactive door remains closed, except in instances when a width greater than or equal to the width of the active door and less than or equal to the width of the double entrance doorway is required, such as, for example, for delivery of furniture and/or equipment that cannot fit through the double entrance doorway. If large objects, such as furniture and/or equipment must pass through the double entrance doorway, both the normally inactive door and the

20

active door of the doorway are opened, to create a wide entrance way, through which the furniture and/or equipment may pass.

Mating edges of the inactive door and the active door do not typically contact one another directly, but are separated by an astragal, the astragal being attached to the edge of an inactive leaf, the astragal extending the length of the inactive door, cushioning the closing of the active door and associated inactive leaf of the doorway, and sealing gaps between the inactive door and the active door.

The astragals often have upper and lower bolt-slide assemblies, which lock the astragals and the inactive doors to upper and lower portions of a door frame surrounding the double entrance door way. The upper and lower bolt-slide assemblies have bolts, which slide within upper and lower ends of the astragal, and are pushed outwardly from the inactive door to extend beyond the ends of the astragal, and are received by upper and lower apertures in the upper and lower portions of the door frame, also known as the header and threshold sill, respectively, to lock the inactive door in place.

Stationary seals are typically used at the lower end of the astragals for sealing and preventing drafts from entering the residential homes and/or commercial buildings through the double entrance doorways at the threshold sill. Since many different types, sizes, and shapes of thresholds are used, the drafts remain an unwanted by product of using the stationary sills. In many instances, the fixed size of the seals, and the materials used, for the stationary seals, are either too thick or too thin to fill the gap

between the lower end of the astragal and the threshold sill, and, thus, result in not providing an adequate seal, and/or the seal degrading over time.

There is thus a need for a self positioning astragal seal that prevents unwanted drafts, is  
5 easy to use and install in a quick, convenient, and efficient manner, is durable and long lasting, maintains its seal against drafts over time, even in situations where repeated opening and closing of the inactive door is necessary, and can be used with a variety of astragals and threshold sills, types, sizes, and shapes of threshold sills, doors, and door frames.

10

The self positioning astragal seal should be capable of automatically positioning at least one seal at the lower end of the astragal adjacent the threshold sill, and prevent drafts at the vicinity of the lower end of the astragal and the threshold sill, and/or of automatically positioning at least one seal at the upper end of the astragal adjacent the  
15 header, and prevent drafts at the vicinity of the header.

20

The self positioning astragal seal should independently position itself abuttingly adjacent the sill and/or the header when the bolts are extended from a retracted position to an extended position and are received by the upper and/or lower apertures in the upper and/or lower portions of the door frame.

Different astragals have heretofore been known. However, none of the astragals adequately satisfies these aforementioned needs.

U.S. Patent No. 5,857,291 (Headrick) discloses an astragal with integral sealing lock block, for use with a double door installation, which includes an astragal strip secured along a vertical edge of an inactive door. A lock block is slidably  
5 disposed in at least one end of the astragal strip, and can be moved between an extended position, for securing the inactive door, and a retracted position for freeing the inactive door. The lock block has a projecting bolt receivable in a receptacle in a door frame, when the lock block is slid to its extended position. A gasket is secured to an end of the lock block, and the bolt passes through an  
10 opening in the gasket. The gasket engages and seals against the door frame, when the lock block is in its extended position. Gaskets are also provided on the sides of the lock block, for engaging and sealing against the doors of the double door installation. When the doors are closed and secured in place, the lock block and gasket assembly prevents drafts from flowing under the door  
15 installation beneath the astragal thereof.

U.S. Patent Nos. 5,350,207 and 5,328,217 (Sanders) disclose locking astragals, for attaching to an inactive leaf of a double doorway, and in particular U.S. Patent No. 5,350,207. Each of the locking astragals has an elongated astragal  
20 casing, which has a channel and bolt-slide assemblies mounted slidably within the channel. Each bolt-slide assembly includes a latching member and bolt. By depressing the latching member, the latching member can slide through the channel, to extend and lock the bolts into indentations in upper and lower

surfaces of a door frame. The bolts may also be retracted back into the astragal, to open the inactive leaf. Each of the latching members has an integral spring, which simplifies fabrication and assembly.

5 U.S. Patent No. 6,491,326 (Massey, et al) discloses a swing adaptable astragal with lockable unitary flush bolt assemblies, for double door entryways, which includes an extruded aluminum frame into which upper and lower flush bolt assemblies are slidably disposed. The flush bolt assemblies include a long metal bolt about which is injection overmolded a series of retainer guides,  
10 which ride in the frame. Locking mechanisms are also integrally overmolded onto the bolts. The frame and all components of the astragal assembly are symmetrical and reversible, so that the assembly is non-handed; that is, it can be adapted to both a right hand swing and a left-hand swing inactive door. A strike plate mounting system and bottom-sealing block are provided, and the upper  
15 end of the assembly includes means for sealing against a stop of a head jamb. Drafts at upper and lower inside corners of the doors of a double door entryway may be prevented.

U.S. Patent No. 6,125,584 (Sanders) discloses an automatic door bottom for a  
20 hinged door, which is pivotable to be positioned over a sill when closed, the door having a hinge side and a width, the door bottom having an inverted channel having an open bottom, a length corresponding to the door width and a hinge end corresponding to the hinge side of the door; a sealing member having

a length corresponding to the length of the channel, the sealing member being housed in the channel and being movable vertically downwardly into a sealing position, in which the sealing member contacts the sill when the door is closed; and a displacement mechanism installed in the channel and coupled to the  
5 sealing member, for moving the sealing member vertically into the sealing position in response to closing of the door, wherein the displacement mechanism is coupled to the sealing member at a plurality of points along the length of the sealing member, and is operative to move the end of the sealing member at the hinge side of the channel into the sealing position, prior to the  
10 remainder of the sealing member, during closing of the door.

U.S. Patent No. 6,457,751 (Hartman) discloses a locking assembly for an astragal, which can be attached to an inactive door of a double door unit of a residence or a building. The astragal is attached to an edge of the inactive door  
15 in space between the inactive door and active door. A separate locking assembly is attached adjacent a top end of the door and also adjacent a bottom end of the door. A plug having an elongated locking bolt extending therefrom is mounted in a front end of a carriage member. Additional structure is provided for reciprocal travel of the carriage member between a locked position  
20 and an unlocked position.

U.S. Patent No. 5,335,450 (Procton) discloses an astragal, which has an exterior aluminum extrusion and an interior wooden portion. The exterior extrusion

includes a pair of rearwardly extending center walls, which form a channel for receiving the wooden interior portion. Attachments and door hardware can be installed in the wooden interior portion, while the extruded exterior acts as cladding.

5

U.S. Patent No. 5,590,919 (Germano) discloses a T-astragal and sleeve for door, for use with double swinging doors, such as for french doors. The T-astragal includes a cap portion perpendicular to a base portion, wherein both the cap and base can be formed from wood, such as plywood or plastic. The T-astragal is a molding that extends the full height of the swinging doors. One side of the base portion is fixably coupled to the free end of one of the swinging doors by nails or screws. The free end of the other swinging doors is able to swing up to and against a shoulder portion formed from the cap and base portions. A metal pipe shaped sleeve having an approximate length of one foot is partially positioned along the longitudinal axis of the T-astragal molding. A bolt slides within the sleeve from a rest position to an extended position, where the extended position locks the attached door to a matching slot in the door frame.

10

15

20

U.S. Patent No. 4,429,493 (St. Aubin) discloses an astragal housing seal and lock, for use in a double door assembly having an active door and a relatively inactive door. The astragal has a vertically extending mullion housing, which is attached to a free edge of the relatively inactive door. A vertically extending

slide section is mounted on the mullion housing on a sealing side of the free edge of the inactive door. The slide section extends from the free vertical edge of the inactive door, when the active door is in the closed position. The slide section is vertically movable from an unlocked position to a locked position, wherein the slide section is moved vertically downward, with respect to the mullion housing, to engage the sill/threshold of the door frame, thereby preventing movement of the inactive door.

U.S. Patent No. 4,058,332 (DiFazio) discloses an astragal and flush bolt assembly to be secured to a relatively stationary member such as a door jamb or to the edge of an inactive door of a pair of double doors or the like. The astragal assembly includes a flat metal body mounted on the edge of the stationary member and a metal stop member secured to the body along one edge thereof. The flat body includes first and second spaced apart legs extending outwardly from the stationary member, with the flat body and legs defining a channel to receive and retain a door latch bolt from the active door. The stop member prevents movement of the door in a first direction, and when the latch bolt is engaged in the channel, the channel and latch bolt prevent the door from moving in the opposite direction. A pair of flush bolts are slidably mounted in the channel, one adjacent each end thereof, so that when the astragal assembly is utilized with double doors, the flush bolts are moved to engage the header and sill, respectively, to hold the inactive door stationary. The astragal body is secured to the stop member by a thermal barrier or thermal break



structure, to provide thermal insulation between the inside and the outside of the doors. The stop member also includes a weather strip to form a seal against the active door, and when metal doors or metal covered doors are used, the weather strip may include a magnetic member to form a seal against the active door.

5

U.S. Patent No. 6,453,616 (Wright) discloses an astragal for use with exterior double door installations, such as french doors. When attached to the edge of a generally inactive door, the astragal provides a door stop for an active door, a seal to prevent intrusion of water, and a lock for the inactive door. The invention particularly pertains to extruded metal astragals, capable of increasing the resistance of the double door system to high wind conditions. The astragal comprises a longitudinally extending base member that has at least one longitudinally extending channel and a pair of spaced apart outwardly extending legs. At least one bolt is slidably inserted in the channel adjacent to one of the first and second ends of the channel. The astragal is attached to the door, by at least one cleat whose spaced apart arms engage the legs of the base member, providing resistance to the astragal rocking in relation to the door edge, when the doors are subject to wind forces.

10

15

20

U.S. Patent No. D293,719 discloses a combined astragal extrusion and seal.

For the foregoing reasons, there is a need for a self positioning astragal seal that prevents unwanted drafts, is easy to use and install in a quick, convenient, and efficient

manner, is durable and long lasting, maintains its seal against drafts over time, even in situations where repeated opening and closing of the inactive door is necessary, and can be used with a variety of astragals and threshold sills, types, sizes, and shapes of threshold sills, doors, and door frames. The self positioning astragal seal should be

5 capable of automatically positioning at least one seal at the lower end of the astragal adjacent the threshold sill, and prevent drafts at the vicinity of the lower end of the astragal and the threshold sill, and/or of automatically positioning at least one seal at the upper end of the astragal adjacent the header, and prevent drafts at the vicinity of the header. The self positioning astragal seal should independently position itself

10 abuttingly adjacent the sill and/or the header when the bolts are extended from a retracted position to an extended position and are received by the upper and/or lower apertures in the upper and/or lower portions of the door frame.

## SUMMARY

The present invention is directed to a self positioning astragal seal that automatically positions at least one seal at the lower end of an astragal adjacent the threshold sill of a door frame, and prevent drafts at the vicinity of the lower end of the astragal and the threshold sill, and/or of automatically positions at least one seal at the upper end of the astragal adjacent the header of the door frame, and prevent drafts at the vicinity of the header. The self positioning astragal seal independently positions itself abuttingly adjacent the sill and/or the header when the astragal's bolts are extended from a retracted position to an extended position and are received by the upper and/or lower apertures in the upper and/or lower portions of the door frame. The self positioning astragal seal prevents unwanted drafts, is easy to use and install in a quick, convenient, and efficient manner, is durable and long lasting, maintains its seal against drafts over time, even in situations where repeated opening and closing of the inactive door is necessary, and can be used with a variety of astragals and threshold sills, types, sizes, and shapes of threshold sills, doors, and door frames.

A self positioning astragal seal, for use with an astragal having a bolt having a bolt retracted position and a bolt extended position, having features of the present invention comprises: a seal block having a catch and a hole, the bolt slidably disposed through the hole, the catch catching a portion of the bolt and holding the seal block in a seal block retracted position when the bolt is in the bolt retracted position and releasing the seal

block when the bolt is in the bolt extended position; spring means forcing the seal block into a seal block extended position when the seal block is released.

An astragal having a self positioning astragal seal having features of the present  
5 invention comprises: an astragal body; a bolt having a bolt retracted position and a bolt extended position; a seal block having a catch and a hole, the bolt slidably disposed through the hole, the catch catching a portion of the bolt and holding the seal block in a seal block retracted position when the bolt is in the bolt retracted position and releasing the seal block when the bolt is in the bolt extended position; spring means forcing the  
10 seal block into a seal block extended position when the seal block is released.

## DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and

5 accompanying drawings where:

FIG. 1 is a perspective view of a self positioning astragal seal, constructed in accordance with the present invention, shown extended;

FIG. 2 is a perspective view of the self positioning astragal seal, shown retracted;

FIG. 3 is an exploded view of the self positioning astragal seal and a latching  
10 mechanism;

FIG. 4 is an exploded view of selected components of the self positioning astragal seal and a portion of the latching mechanism of FIG. 3;

FIG. 5 is an exploded view of the latching mechanism of FIG. 3;

FIG. 6 is a perspective view of entrance doors, comprising an inactive door, shown  
15 in a closed position, and an active door;

FIG. 7 is a perspective view of the inactive door, showing the self positioning astragal seal and an astragal installed thereon the inactive door, with the self positioning astragal seal extended;

FIG. 8 is a section view of the self positioning astragal seal, shown extended;

20 FIG. 9 is another section view of the self positioning astragal seal, shown extended;

FIG. 10 is another section view of the self positioning astragal seal, with the self positioning astragal seal extended;

FIG. 11 is another section view of the self positioning astragal seal, with the self positioning astragal seal extended;

FIG. 12 is another section view of the self positioning astragal seal, with the self positioning astragal seal extended;

5 FIG. 13 is another section view of the self positioning astragal seal, with the self positioning astragal seal extended;

FIG. 14 is another section view of the self positioning astragal seal, with the self positioning astragal seal extended;

10 FIG. 15 is a section view of the latching mechanism of FIG. 3, along a portion of line 8-8 of FIG. 7, with the self positioning astragal seal extended;

FIG. 16 is a section view of the self positioning astragal seal, along a portion of line 8-8 of FIG. 7, with the self positioning astragal seal extended;

FIG. 17 is a section view of the self positioning astragal seal, shown retracted;

FIG. 18 is another section view of the self positioning astragal seal, shown retracted;

15 FIG. 19 is an exploded view of an upper bolt and latching mechanism of the astragal of FIG. 7.

FIG. 20 is a section view of the self positioning astragal seal shown with an alternate embodiment of an astragal installed thereon the inactive door;

20 FIG. 21 is a section view of the self positioning astragal seal shown with an alternate embodiment of an astragal installed thereon the inactive door;

FIG. 22 is a section view of the self positioning astragal seal shown with an alternate embodiment of an astragal installed thereon the inactive door, and also showing the active door;

FIG. 23 is a section view of the self positioning astragal seal shown with an alternate embodiment of an astragal installed thereon the inactive door, and also showing the active door;

FIG. 24 is a section view of the self positioning astragal seal shown with an alternate embodiment of an astragal installed thereon the inactive door, and also showing the active door; and

FIG. 25 is a section view of the self positioning astragal seal shown with an alternate embodiment of an astragal installed thereon the inactive door, and also showing the active door.

10

## REFERENCE NUMERALS

These and other features, aspects, and advantages of the present invention will become better understood with regard to the references and associated reference numerals of the

5 following description and accompanying drawings where:

- 10** self positioning astragal seal
- 12** seal block
- 14** seal block hole
- 16** shoulder
- 10 **18** compression spring
- 20** end seal
- 30** astragal
- 42** inactive door edge
- 44** inactive door
- 15 **46** sill
- 48** door frame
- 52** elongated guide
- 54** elongated guide channel
- 56** lower bolt
- 20 **58** shoulder
- 60** astragal bottom
- 74** seal block bottom
- 78** seal block base



	<b>80</b>	face plate
	<b>82</b>	guide block
	<b>84</b>	"T" shaped member
	<b>86</b>	compression spring guide holder
5	<b>88</b>	compression spring bottom end
	<b>90</b>	base top
	<b>92</b>	barrel
	<b>94</b>	barrel extension
	<b>96</b>	barrel extension arcuate interior
10	<b>98</b>	extension
	<b>100</b>	extension arcuate interior
	<b>102</b>	T top portion
	<b>104</b>	arcuate interior
	<b>105</b>	angled edges
15	<b>106</b>	shoulder
	<b>108</b>	face plate reinforcement
	<b>110</b>	face plate stop
	<b>112</b>	guide block edge stop
	<b>114</b>	guide block reinforcement
20	<b>116</b>	guide block stop
	<b>130</b>	astragal recess
	<b>132</b>	astragal extension stop
	<b>134</b>	astragal retraction stop

	<b>136</b>	astragal opposing side
	<b>138</b>	astragal side portion
	<b>140</b>	astragal side
	<b>142</b>	side channel
5	<b>144</b>	threaded hole
	<b>146</b>	threaded hole
	<b>148</b>	set screw
	<b>150</b>	angled longitudinal channel edge
	<b>152</b>	compression spring top end
10	<b>154</b>	seal hole
	<b>156</b>	face seal
	<b>158</b>	face plate exterior side
	<b>160</b>	active door edge
	<b>162</b>	active door
15	<b>164</b>	header
	<b>166</b>	seal peel off adhesive strip
	<b>168</b>	face seal peel off adhesive strip
	<b>180</b>	astragal housing
	<b>182</b>	longitudinal channel
20	<b>184</b>	longitudinal retention guide
	<b>185</b>	channel base
	<b>186</b>	lockset strike
	<b>188</b>	deadbolt strike

	<b>190</b>	upper bolt
	<b>191</b>	upper bolt assembly
	<b>192</b>	lockset
	<b>194</b>	deadbolt
5	<b>196</b>	lockset cover plate
	<b>198</b>	deadbolt cover plate
	<b>199</b>	screws
	<b>200</b>	latching member
	<b>202</b>	pull block
10	<b>204</b>	elongated connector
	<b>206</b>	compression spring
	<b>208</b>	slide plate
	<b>210</b>	bolt lower portion
	<b>212</b>	bolt mid portion
15	<b>214</b>	bolt upper portion
	<b>216</b>	bolt slot
	<b>218</b>	bolt hole
	<b>220</b>	end pin
	<b>222</b>	elongated connector hole
20	<b>224</b>	pin
	<b>226</b>	pin
	<b>228</b>	pull block track
	<b>230</b>	pull block retention track

	<b>232</b>	pull block retention track
	<b>234</b>	pull block channel
	<b>236</b>	pull block channel
	<b>238</b>	pull block notch
5	<b>240</b>	pull block base
	<b>242</b>	pull block notch
	<b>244</b>	pull block bearing notch
	<b>246</b>	pull block notch side
	<b>248</b>	lever arm receiving hole
10	<b>250</b>	lever arm
	<b>252</b>	trunnion
	<b>254</b>	spring tail
	<b>256</b>	latching dog
	<b>260</b>	slide plate retraction hole
15	<b>262</b>	slide plate extension hole
	<b>264</b>	slide plate notch
	<b>266</b>	slide plate end tab
	<b>268</b>	slide plate projecting tab
	<b>270</b>	slide plate projecting notch
20	<b>280</b>	elongated guide notched recess
	<b>282</b>	elongated guide end
	<b>284</b>	pull block arrow marking
	<b>286</b>	arcuate side

	<b>288</b>	arcuate base
	<b>300</b>	alternate astragal housing
	<b>302</b>	saw tooth recess
	<b>304</b>	finned tail
5	<b>306</b>	foam weather strip
	<b>308</b>	cavity
	<b>310</b>	alternate astragal housing
	<b>312</b>	thermal break
	<b>314</b>	slot
10	<b>320</b>	alternate astragal
	<b>322</b>	alternate astragal housing
	<b>324</b>	cover
	<b>326</b>	outer seal
	<b>328</b>	inner seal
15	<b>330</b>	alternate astragal
	<b>332</b>	thermal break
	<b>340</b>	alternate astragal
	<b>342</b>	cover element
	<b>344</b>	saw tooth recess
20	<b>346</b>	finned tail
	<b>348</b>	weather strip seal
	<b>349</b>	inner seal
	<b>350</b>	alternate astragal

**352**    thermal break

## DESCRIPTION

5 The preferred embodiments of the present invention will be described with reference to  
FIGS. 1-25 of the drawings. Identical elements in the various figures are identified with  
the same reference numbers.

FIGS. 1-19 show an embodiment of the present invention, a self positioning astragal  
10 seal **10**, which comprises a seal block **12** having a substantially centrally disposed hole  
**14** therethrough, a shoulder **16**, compression springs **18**, and end seal **20**, for use with  
an astragal **30**.

The astragal **30** is mounted to edge **42** of inactive door **44**, and the self positioning  
15 astragal seal **10** is mounted to the astragal **30** adjacent sill **46** of door frame **48**, as  
shown in FIGS. 6 and 7. The astragal **30** has an elongated guide **52** having a  
substantially centrally disposed longitudinal channel **54** and a bolt **56** having a shoulder  
**58**, the bolt **56** slidably mounted therein the substantially centrally disposed longitudinal  
channel **54**.

20

The astragal seal shoulder **16** catches the bolt shoulder **58** when the bolt **56** is retracted  
to a retracted position, as shown in FIGS. 2, 17, and 18, and is released from the bolt  
shoulder **58** when the bolt **56** is extended to an extended position, as shown in FIGS. 1

and 7-16, the compression springs **18** forcing the seal block **12** into an extended position, when the bolt **56** is in the bolt extended position. The seal block **12** is, thus, retracted to a retracted position, the astragal seal shoulder **16** catching and abutting the bolt shoulder **58**, and holding the seal block **12** in a seal block retracted position when  
5 the bolt **56** is in the bolt retracted position. The seal block **12** is extended to the seal block extended position, when the astragal seal shoulder **16** is released from the bolt shoulder **58**, the compression springs **18** forcing the seal block **12** into the seal block extended position, when the bolt **56** is in the bolt extended position. The astragal seal shoulder **16**, thus, acts as a catch, which catches the bolt shoulder **58** when the bolt **56** is  
10 retracted to the bolt retracted position, and is released from the bolt shoulder **58** when the bolt **56** is extended to the bolt extended position.

The self positioning astragal seal **10** automatically and independently adjusts itself to fit snugly and fill any gaps between bottom **60** of the astragal **30** and the sill **46** of the door  
15 frame **48**, when the bolt **56** is in the bolt extended position, thus, preventing unwanted drafts between bottom **74** of the seal block **12** and the sill **46** of the door frame **48**, the compression springs **18** forcing the seal block **12** opposingly away from the bottom **60** of the astragal **30** and forcing the end seal **20**, which is affixed to the bottom **74** of the seal block **12**, to abut the sill **46** of the door frame **48**.

20

The seal block **12** has base **78**, face plate **80**, and guide block **82**, which is adjacent the inactive door edge **42**, when the self positioning astragal seal **10** and the astragal are installed on the inactive door **44** and the seal block **12** is in the retracted position, the



face plate **80** and the guide block **82** being substantially perpendicular to the base **78**, and substantially parallel one to the other.

The seal block **12** has substantially "T" shaped member **84** integral with the guide block  
5 **82** and compression spring guide holders **86**, which hold the compression springs **18** in place, the compression springs **18** being mounted about the compression spring holders **86**, with bottom ends **88** of the compression springs **18** abutting top **90** of the base **78**.

The seal block **12** has barrel **92** integral with the guide block **82**, the barrel **92** having the substantially centrally disposed hole **14** therethrough to the bottom **74** of the seal  
10 block **12**, the bolt **56** slidable therethrough the substantially centrally disposed hole **14**, and the seal block **12** slidable about the bolt **56**. The barrel **92** has extension **94**, which is integral with the barrel **92**, having arcuate interior **96**, which is substantially collinear with the interior of the barrel **92**, and extension **98** having the shoulder **16** and arcuate interior **100**. The substantially "T" shaped member **84** has T top portion **102**, which has  
15 arcuate interior **104**, angled edges **105**, and shoulder **106**. The face plate **80** has reinforcements **108** having stops **110**. The guide block **82** has edge stops **112** and reinforcements **114** having stops **116**. The compression spring holders **86** have splines for reinforcement.

20 The elongated guide **52** of the astragal **30** has recesses **130**, which have extension stops **132** and retraction stops **134** at opposing ends thereof, and substantially planar opposing side **136**. The elongated guide **52** of the astragal **30** has substantially planar side portions **138** adjacent the recesses **130**, which oppose the substantially planar opposing

side **136**, and sides **140**, which are substantially perpendicular to the substantially planar side portions **138**, the recesses **130**, and the substantially planar opposing side **136**. The elongated guide **52** also has opposing longitudinally disposed side channels **142**. The substantially planar side portions **138** and the substantially planar opposing side **136**  
5 have threaded holes **144** and **146**, respectively, therethrough, opposing one another, having set screws **148** therein, the set screws **148** extending across the longitudinally disposed side channels **142**. The elongated guide **52** also has angled longitudinal edges **150** atop the substantially centrally disposed longitudinal channel **54** adjacent the recesses **130** and the substantially planar side portions **138**.

10

The substantially "T" shaped member **84** and the face plate **80** of the seal block **12** matingly sandwich the recesses **130** and the substantially planar opposing side **136** of the astragal **30**, respectively, therebetween, and retain the seal block **12** slidably mating about the elongated guide **52** between the seal block retracted position and the seal  
15 block extended position, and vice versa.

20

The compression springs **18** are mounted about the compression spring holders **86**, with the bottom ends **88** of the compression springs **18** abutting the top **90** of the base **78** of the seal block **12** and top **152** of the compression springs **18** abutting the set screws **148**  
in the longitudinally disposed side channels **142** of the astragal **30**. The compression springs **18** are held in the longitudinally disposed side channels **142** of the astragal **30** under compression, the extension stops **132** of the astragal **30** preventing the

compression springs **18** from forcing the substantially "T" shaped member **84** out of the recesses **130**.

The barrel **92** of the seal block **12** is matingly slidable about the bolt **56** of the astragal  
5 **30**, and the bolt **56** is matingly slidable therethrough the substantially centrally disposed  
hole **14** of the barrel **92** of the seal block **12**. The angled edges **105** of the substantially  
"T" shaped member **84** matingly abut the angled longitudinal edges **150** of the astragal  
**30**. The angled edges **105** of the substantially "T" shaped member **84** and the barrel **92**  
of the guide block **82** guide the seal block **12** collinearly with the angled longitudinal  
10 edges **150** of the astragal **30** and the substantially centrally disposed longitudinal  
channel **54**, the bolt **56** being substantially aligned with the substantially centrally  
disposed longitudinal channel **54**.

The extension stops **132** and the retraction stops **134** limit the extent of travel of the  
15 substantially "T" shaped member **84**, and, thus, limit the extent of travel of the seal  
block **12** and the end seal **20** from the seal block extended position to the seal block  
retracted position, respectively, the compression springs **18** forcing the seal block **12**  
into the extended position, other than when the seal block **12** is retracted. The seal  
block **12** is retracted to the retracted position, the astragal seal shoulder **16** catching and  
20 abutting the bolt shoulder **58**, and holding the seal block **12** in the seal block retracted  
position, when the bolt **56** is in the bolt retracted position. The seal block **12** is  
extended to the seal block extended position, when the astragal seal shoulder **16** is

released from the bolt shoulder **58**, the compression springs **18** forcing the seal block **12** into the seal block extended position, when the bolt **56** is in the bolt extended position.

The end seal **20** has substantially centrally disposed hole **154** therethrough, which is  
5 substantially aligned collinearly with the substantially centrally disposed hole **14** of the seal block **12**, which allows the end seal **20** to slide about the bolt **56**, and vice versa.

The self positioning astragal seal **10** has face seal **156**, which is affixed to exterior side **158** of the face plate **78** of the seal block **20** and abuts edge **160** of active door **162**,  
when the active door **162** is closed abuttingly against the inactive door **44**, thus,  
10 preventing unwanted drafts between the self positioning astragal seal **10** and the edge **160** of the active door **162**. The astragal **30** also has edge seal **163**.

The self positioning astragal seal **10** may be used with the astragal **30** adjacent the sill **46** and/or header **164** of the door frame **48**, and may be used with the inactive door **44**  
15 and/or the active door **162**. Typical installations, however, have the astragal **30** mounted to the edge **42** of the inactive door **44**, and the self positioning position astragal end seal **20** mounted to the astragal **30** adjacent the sill **46**.

The self positioning astragal seal **10** may be used with a variety of astragals but is  
20 preferably used with the astragal **30** shown in the accompanying figures. Other astragals may be modified to suit the needs of particular applications.

The end seal **20** and the face seal **156** may have adhesives covered by peel off adhesive strips **166** and **168**, respectively, the end seal **20** and the face seal **156** being fastened to the seal block **12** with the adhesives, upon removal of the adhesive strips **166** and **168**, respectively.

5

The astragal **30** has astragal housing **180** having longitudinal channel **182**, which has longitudinal retention guides **184**, the elongated guide **52** inserted into the longitudinal channel **182** and held in the longitudinal channel **182** by the retention guides **184** and the set screws **148**, and channel base **185**, the set screws **148** locking the elongated  
10 guide **52** into the astragal housing **180**. The astragal **30** also has lockset strike **186**, deadbolt strike **188**, and upper bolt **190** mounted to the longitudinal channel **182** of the astragal housing **180**, the bolt **56** and the upper bolt **190** being used to lock the astragal **30**, and, thus, the inactive door **44**, which the astragal **30** is affixed to, to the sill **46** and the header **164**, respectively, of the door frame **48**. The upper bolt **190** may be used  
15 with the self positioning astragal seal **10** and/or alternatively the upper bolt **190** may use an alternative sealing means. Upper bolt assembly **191** having the upper bolt **190** is installed into the longitudinal channel **182** in substantially the same manner as the elongated guide **52**. The active door **162** has lockset **192** and deadbolt **194**, which are received by lockset strike **186**, deadbolt strike **188**, respectively, on the inactive door  
20 **44**, for securing the active door **162** to the inactive door **134** when the active door **162** is closed abuttingly adjacent the inactive door **44**. The astragal housing **180** has lockset cover plate **196** and deadbolt cover plate **198**, which are mounted to the astragal

housing **180**, the lockset strike **186** and the deadbolt strike **188** being fastened to the lockset cover plate **196** and the deadbolt cover plate **198** with screws **199**.

The astragal **30** has latching member **200**, pull block **202**, elongated connector **204**,  
5 compression spring **206** about the elongated connector **204**, and slide plate **208**. The bolt **56** has lower portion **210**, mid portion **212** adjacent the shoulder **58**, the mid portion **212** having a smaller diameter than the diameter of the lower portion **210**, and upper portion **214**, the upper portion **214** of the bolt **56** having substantially the same diameter as the lower portion **210**, and having a slot **216** therethrough and a hole **218**  
10 therethrough, the slot **216** and the hole **218** substantially perpendicular one to the other.

The elongated connector **204** has end pin **220**, opposing hole **222**, and pin **224** therebetween, the end pin **220** and the pin **224** substantially perpendicular to the plane of the elongated connector **204**. The elongated connector **204** is sandwiched in the slot  
15 **216** of the upper portion **214** of the bolt **56**, the hole **218** and the hole **222** aligned one with the other, the bolt **56** and the elongated connector **204** pinned one to the other with pin **226**, the pin **226** therethrough the holes **222** and **218**.

The pull block **202** has longitudinal tracks **228**, retention tracks **230** and **232**, and  
20 channels **234** and **236**, the channels **234** between the longitudinal tracks **228** and the retention tracks **230**, and the channels **236** between the longitudinal tracks **230** and the retention tracks **232**. The pull block **202** is inserted into the longitudinal channel **182** of the astragal housing **180**, the channels **234** and **236** being adjacent to the retention

guides **184** of the astragal housing **180**, the retention guides **184** slidably retaining the pull block **204** in the astragal housing **180**. The pull block **202** has substantially centrally disposed notch **238** at base **240** of the pull block **202**, notch **242** adjacent and substantially perpendicular to the substantially centrally disposed notch **238**, and bearing notches **244**. The substantially centrally disposed notch **238** is adjacent to and surrounds the elongated connector **204** adjacent the end pin **220** of the elongated connector **204**; and sides **246** of the notch **242** surround and abut the end pin **220**, thus, pinning the elongated connector **204** to the pull block **202** one to the other. The pull block **202** also has lever arm receiving hole **248**.

10

The latching member **200** has lever arm **250**, which has trunnions **252** protruding therefrom, spring tail **254**, and latching dog **256**.

The slide plate **208** has retraction hole **260**, extension hole **262**, notches **264**, which form end tabs **266**, and projecting tabs **268**, which form projecting notch **270** therebetween, the projecting notch **270** for matingly slidably receiving the elongated connector **204** therebetween.

The elongated guide **52** is locked into the astragal housing **180** with the set screws **148**. The elongated guide **52** has notched recesses **280** opposing the recesses **130**, the notched recesses **280** matingly receiving the end tabs **266** of the slide plate **208** therein, and adjacent ends **282**, the notches **264** of the slide plate **208** matingly receiving the ends **282** of the elongated guide **52** therein, the slide plate **208** being sandwiched and

locked between the elongated guide **52** and the channel base **185** of the astragal housing **180**. The projecting notch **270** of the slide plate **208** slidably guides the elongated connector **204**, which is located in the projecting notch **270**, substantially collinear with the center line of the elongated guide **52**.

5

The latching member **200** is sandwiched between the pull block **202** and the slide plate **208**, with the trunnions **252** in the bearing notches **244** of the pull block **202** and the lever arm **250** extending through the lever arm receiving hole **248** of the pull block **202**, thus facilitating operator control.

10

The retraction hole **260** and the extension hole **262** of the latching member **200** matingly receive the latching dog **256** of the latching member **200** therein.

The latching member **200** may be retracted to a latching member retracted position,  
15 when the lever arm **250** of the pull block **202** is depressed and pushed in the direction of pull block arrow marking **284**, which pulls the elongated connector **204** in the direction of the pull block arrow marking **284**, pulls the bolt **56** into the bolt retracted position, pulls the seal block **12** into the seal block retracted position, compresses the compression springs **18**, and compresses the compression spring **206** between the pin  
20 **224** of the elongated connector **204** and the projecting tabs **268** of the slide plate **208**.  
When the latching member **200** is retracted to the latching member retracted position, the spring tail **254** of the latching member **200** forces the latching dog **256** into the



retraction hole **260** of the slide plate **208**, thus, locking the bolt **56** into the bolt retracted position and locking the seal block **12** into the seal block retracted position.

The latching member **200** may be released into a latching member extended position  
5 from the latching member retracted position, when the lever arm **250** of the pull block **202** is depressed and released, releasing compression from the compression spring **206** between the pin **224** of the elongated connector **204** and the projecting tabs **268** of the slide plate **208**, forcing the elongated connector **204** in the direction opposing the pull block arrow marking **284**, forcing the bolt **56** into the bolt extended position, releasing  
10 compression on the compression springs **18**, which forces the seal block **12** into the seal block extended position. When the latching member **200** is released, the latching member **200** snaps into latching member extended position, the latching dog **256** snaps into the extension hole **262** of the slide plate **208**, the spring tail **254** of the latching member **200** forcing the latching dog **256** into the extension hole **262**, thus, locking the  
15 bolt **56** into the bolt extended position with the seal block **12** in the seal block extended position, the seal block **12** automatically and independently self positioned with the end seal **20** abutting the sill **46** of the door frame **48**. The latching member **200** may alternatively be pushed into the latch member extended position.

20 The substantially centrally disposed longitudinal channel **54** of the elongated guide **52** has arcuate sides **286** and arcuate base **288** to slidably and matingly accommodate the bolt **56**, the lower portion **210** and the mid portion **212** of which are substantially cylindrical and have substantially the same diameter. The mid portion **212** of the bolt

**56** is also substantially cylindrical, but has a smaller diameter than the diameter than that of the lower portion **210** and the upper portion **214**.

The astragal housing **180** and the elongated guide **52** are preferably of metal, such as  
5 aluminum or steel, thermoplastics, thermosetting polymers, rubber, or other suitable material or combination thereof.

The seal block **12** and the latching member **200** are preferably injection molded from an engineered plastic resin that has properties to provide flexural strength, such as an  
10 acetal, although other suitable materials may be used. The end seal **20** and the face seal **156** are preferably of cellular material, such as closed cell neoprene sponge, although other suitable materials may be used.

FIG. 15 shows the latching member **200** with the lever arm **250** depressed and the  
15 latching dog **256** ready to be moved to the retraction hole **260** of the slide plate **208**, which is shown after being moved in FIGS. 17 and 18. The seal block **12** is also retracted along with the bolt **56**, when the latching dog **256** is moved into the retraction hole **260**, as shown in FIGS. 17 and 18.

20 The active door **162** and the inactive door **44** are "handed" as either right hand, in which the hinges of the active door **162** are on the right side of the active door **162** as viewed from the outside of the door frame **48** and left hand if the hinges of the active door **162** are on the left side of the door frame **48** as viewed from the outside of the door frame

48. The elongated guide **52** and the self positioning astragal seal **10** may easily be reversed from left hand to right hand, and vice versa, by merely loosening the set screws **148**, removing the elongated guide **52** with the self positioning astragal seal **10** from the longitudinal channel **182** of the astragal housing **180**, and installing the  
5 elongated guide **52** with the self positioning astragal seal **10** on the end of the astragal housing **180** opposing that from which it was removed, thus, converting the astragal **30** from one hand to the other.

FIGS. 20-25 show alternate embodiments of astragals having astragal housings that the  
10 self positioning astragal **10** may be used with, although other suitable astragals having other suitable astragal housings may be used.

FIG. 20 shows an alternate embodiment of an astragal housing **300**, which has a saw-tooth recess **302** to retain finned tail **304** of a typical wrapped foam type weather strip  
15 **306** for sealing. The astragal housing **300** also has cavity **308**.

FIG. 21 shows an alternate embodiment of an astragal housing **310**, which is substantially the same as the astragal housing **300**, except that the astragal housing **310** has thermal break **312**, for installations in climates that experience extremely cold  
20 weather, in which the astragal housing **310** is fabricated from an aluminum extrusion, or other suitable material having substantially the same properties, which would otherwise readily lose heat to the outside and result in condensation, and in some cases even the formation of ice. The thermal break **312** is created by filling cavity **308** of the astragal

housing **300** with a polyurethane thermal break compound, after which it is de-bridged by milling slot **314**, thus, separating outer and inner portions of the astragal housing **310** and preventing infiltration of the cold.

5 FIG. 22 shows an alternate embodiment of an astragal **320**, which may be used for installation on a pair of outswinging rather than inswinging doors, which has astragal housing **322**, cover **324** that provides overlap, and outer seal **326**, and is used on the active leaf of the pair of out swinging doors. Inner seal **328** is of greater reach as the beveled edge of the active door is reversed, creating a greater gap at its inner edge.

10

FIGS. 23 shows an alternate embodiment of an astragal **330**, which may be used for installation on a pair of outswinging rather than inswinging doors, which is substantially the same as the astragal housing **320**, except that the astragal **330** has thermal break **332**.

15

FIG. 24 shows an alternate embodiment of an astragal **340**, which may be used for installation on a pair of outswinging rather than inswinging doors, in which cover element **342** has saw-tooth recess **344** to accommodate finned tail **346** of a wrapped foam weather strip seal **348**. Inner seal **349** is of greater reach as the beveled edge of  
20 the active door is reversed, creating a greater gap at the inner edge.

FIGS. 25 shows an alternate embodiment of an astragal **350**, which may be used for installation on a pair of outswinging rather than inswinging doors, which is

substantially the same as the astragal housing 340, except that the astragal 350 has thermal break 352.

Although the present invention has been described in considerable detail with reference  
5 to certain preferred versions thereof, other versions are possible. Therefore, the spirit  
and scope of the appended claims should not be limited to the description of the  
preferred versions contained herein.